ACID MINE DRAINAGE SOURCE AREA INVESTIGATIONS: 2011-2013

LANDUSKY MINE SITE, MONTANA

David Donohue, P.G. Melissa Schaar, P.G.
HydroSolutions Inc
Helena, Montana
May 1, 2014





Presentation Outline

- * Previous Investigations
- * Source Control and Feasibility
 - * Aquifer Testing
 - * Tracer Tests
 - * Swift Gulch Flows
 - * Hydrograph Analysis
 - * Geochemical Analysis







Project Sponsors

- * Montana DEQ
- * U.S. BLM
- * Montana DNRC






Zortman - Landusky Mine Sites



30-Second Geo-explanation



Fractured Bedrock Aquifer

Generalized Fault Trace Map

shear zone


Α

1650


1600

1550

shear zone



Swift-Alder Structural Trend



Hydrogeologic Investigations - Pre-Source Control Investigation

- * Supplemental EIS 2001
 - * Major reclamation 2002 and 2005
- * Artesian WS-3 Hydrogeology Test 2001
- * Tracer Dye Investigation 2003 and 2004
- * Monitoring Well Installation 2008
- * Aquifer Test 2008
- * Geophysical Investigation 2009

Previous Hydrogeologic Investigations

Investigation results helped identify subsurface conditions:


- * Groundwater flow controlled by complex shear zones with general NE orientation and crosscutting fault structures
- * Shear zones are major conduits for ARD movement from mine complex to Swift Gulch

Source Control Prioritization and Feasibility Evaluation (2011-now)


- * 7-Day Aquifer Test
- * Forced Gradient Dye Tracer Test
- * Natural Gradient Dye Tracer Test
- * Flume Installation and Flow Monitoring in Swift Gulch
- * Mine Water Balance
- * Groundwater Hydrograph Analysis
- * Geochemical Investigation

Why Source Control?






Pumping and Monitoring Well Drawdown during Aquifer test





Monitoring Well Response



Aquifer Test Results

- * Calculated transmissivity values from the aquifer test ranged from 439 to 630 feet²/day, representative of the bulk aquifer (comparable to 2008 48-hour test)
 - * Calculated hydraulic conductivity 8 to 50 feet per day
- * At early pumping times, the flow is dominantly linear with water entering the fracture system from the aquifer at the same rate per unit area
- * As pumping test progresses, flow pattern changes from linear to radial with more discharge derived from the aquifer matrix





Activated carbon sampling packet



Forced Gradient Dye Tracer Test Results

- * Rhodamine breakthrough in ZL-405 in 12 hours
 - * No detection of Rhodamine WT in Swift Gulch after one year
 - * Rhodamine was detected in matrix well ZL-403



Natural Gradient Dye Test Results

- * Eosine detected in BKSP-2E within 3 months (one time detection)
 - * (Travel time was estimated at 2 to 10 months)
- * Eosine detected in downgradient/cross gradient matrix monitoring well ZL-403 within 12 months



Tracer Test Conclusions


- * Dye attenuation likely occurred somewhere in the pathway
- Dye tracer detection in Swift Gulch was very low concentration and likely too diluted to be detected in other Swift Gulch sample locations
- * Delayed arrival of eosine seen in downgradient matrix well is as expected
- * Interaction of the fractures and matrix is evident
- * Rapidly disintegrating quality of downgradient matrix water samples provides evidence for the connection
- * Matrix and shear zones need to be considered as "one whole package" as the remedial alternatives are developed and considered
- * Continual deterioration of the matrix may present new long term geochemical and water quality remediation challenges




Swift Gulch Base Flow Study Results

- * Flow through the upper reaches of Swift Gulch responds directly to and is almost entirely dependent upon snowmelt and precipitation runoff
- * Results of the study indicate that base flow in Swift Gulch increases from the upper most station monitored BKSS-3 to station L-19 through known surface seeps and groundwater discharge
- * In the reach below L-19 to the lower dam, Swift Gulch is identified as a losing reach and appears to lose between 21 gpm to 28 gpm
- * For the period that was monitored, the Swift Gulch water treatment plant has a successful capture rate of 80% at the upper and lower dams

Historical Groundwater Levels




Hydrograph for Monitoring Well ZL-405




Why Geochemical Investigation at Landusky

- * Geochemical data gaps for Northern Landusky Pit wells, general chemistry
- * Expanding/Complementing dye tracer results
- * Traditional Approaches may not capture big picture
- * A multi-isotope approach, along with general chemistry, can characterize source water, flow paths, and groundwater contribution to Swift Gulch

Sulfate and Total Metal Concentrations of Spring BKSP-2E




pH for Landusky Pit Monitoring Wells




Geochemical Parameters and Justifications

Analyte	Justification
Oxygen (18O/16O) Hydrogen (2H/1H)	Estimate the source, water-rock interactions
Strontium (87Sr/86Sr)	Indication of flow path history
Uranium (²³⁴ U/ ²³⁸ U)	Interconnectivity, groundwater flow paths and rates, assess groundwater mixing and volumes, and assess water-rock chemical interactions
Field Parameters: Eh, pH, DO, and SC	Geochemical modeling and metal speciation
Major Cations and Anions, Trace Elements, and Metals	In combination with a multi-isotope approach, useful for characterizing source water, flow paths, and groundwater contribution to surface water

Landusky Monitoring Locations $\delta^{18}O$ H₂O ‰, Seasonal Variations



Plot of ²³⁴U/²³⁸U activity ratio (AR) compared to dissolved uranium concentrations, August 2013



Geochemical Results

- * In general, over time, metals and sulfate concentrations have been increasing and pH has been decreasing in Swift Gulch and groundwater from the northern Landusky Pit monitoring wells
- * Groundwater associated with the Niseka Shear appears to be undergoing geochemical degradation due to continual AMD contributions
- * The uranium isotopic results indicate that the monitoring wells associated with the Niseka Shear are mainly AMD water with the same isotopic signature found in the August-Little Ben pit


Geochemical Conclusions

- * Wells completed in the same fracture system showed different isotopic signatures but similar seasonal variations
- * The different isotopic signatures are attributed to additional deep groundwater mixing as the fracture system extends further from the Landusky Pit Complex
- * The high AR results for the deeper groundwater well ZL-313, and very low aluminum, sulfate, and iron concentrations, suggest that the deeper groundwater is less affected by AMD water
- * AMD does not appear to extend into the adjacent King Creek drainage basin

Future Reclamation Thoughts

- * Installation of large-diameter pumping wells in the Landusky Pit Complex
 - * Assessing the chemistry directly within the reclaimed pits
 - * Provide wells for remedial alternative pilot testing directly in the source areas
- * Water management of Artesian Well WS-3 and monitoring water level response in the Landusky Pit Complex
- Volume control within the Landusky Pit Complex to reduce volume of AMD to Swift Gulch
- In-Situ bio-treatment source control

Historic and Current Water Levels for Monitoring Wells Associated with Artesian Well WS-3, Opened April 9, 2014



Thank you

David Donohue

davidd@hydrosi.com

Melissa Schaar

melissas@hydrosi.com

Helena office: 406-443-6169





www.hydrosi.com

